

Danger

COMPONENT A - BASE : Contains: BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE.; FORMALDEHYDE; OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL; 1,6-HEXANDIOLDIGLYCIDYLETHER; QUARTZ (FINE FRACTION)H315 - Causes skin irritation, H317 - May cause an allergic skin reaction, H319 - Causes serious eye irritation, H411 - Toxic to aquatic life with long lasting effects, H373 - May cause damage to organs (lungs) through prolonged or repeated exposure (Inhalation of dust). P260 - Do not breathe dust-fume/gas/mist/vapours/spray, P264 - Wash hands, forearms and face thoroughly after handling, P272 - Contaminated work clothing should not be allowed out of the workplace, P273 - Avoid release to the environment, P280 - Wear protective clothing, eye protection, face protection, P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

UFI:M82D-MADH-4H0J-6TNT

COMPONENT B - ACTIVATOR : Contains: PHENOL, STYRENATED, 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE, 1,3-BENZENEDIMETHANAMINE, SALICYLIC ACID., QUARTZ (FINE FRACTION) H314 - Causes severe skin burns and eye damage, H317 - May cause an allergic skin reaction, H373 - May cause damage to organs (lungs) through prolonged or repeated exposure (Inhalation of dust), H411 - Toxic to aquatic life with long lasting effects. P260 - Do not breathe dust-fume/gas/mist/vapours/spray, P264 - Wash hands, forearms and face thoroughly after handling, P272 - Contaminated work clothing should not be allowed out of the workplace, P273 - Avoid release to the environment, P280 - Wear protective clothing, eye protection, face protection, P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

UFI: 7VYK-XAXX-UH0S-W8G3



EPOXY 600

CALLIDOR

**MADE IN
BRITAIN**

585ml e

Art.78457




C2



**LEED
TESTED**



**Before Disposal,
any unmixed
product must be
mixed and hardened,**



**IMPORTANT!
CONSULT TDS FOR FULL
INSTALLATION PARAMETERS**

Callidor Ltd.
124 City Road,
London, England, EC1V 2NX
callidor.com
+44 7732 208845.
info@callidor.com

HANDLING AND STORAGE: Store in dry conditions away from direct sunlight between +5°C and +25°C.
STOCKAGE: Stocker dans des conditions sèches à l'abri de la lumière directe du soleil entre +5°C et +25°C.
LAGERUNG: Trocken und vor direkter Sonneneinstrahlung geschützt aufbewahren +5°C und +25°C.
MANIPULACIÓN Y ALMACENAMIENTO: Almacenar en condiciones secas, lejos de la luz solar directa, entre +5°C y + 25°C.



Batch / Expiry - Lot / Expiration
Charges / Ablauf - Lote / Expiración

36676

135mm x 195mm